

# FOUR C FC-W 10W-40

Chemwatch Material Safety Data Sheet  
Issue Date: 8-Jun-2007  
NC317ECP

CHEMWATCH 4688-80  
Version No:1  
CD 2007/2 Page 1 of 8

---

## Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

---

### PRODUCT NAME

FOUR C FC-W 10W-40

### SYNONYMS

### PRODUCT USE

Lubricant.

### SUPPLIER

Company: Anglo Design  
Address:  
2 Beaumont Road  
Mount Kuringai  
NSW, 2080  
AUS  
Telephone: +61 2 9457 8566  
Fax: +61 2 9457 8057

Company: Anglo Design Pty Ltd  
Address:  
PO Box 62  
Mount Kuringai  
NSW, 2080  
AUS

---

## Section 2 - HAZARDS IDENTIFICATION

---

### STATEMENT OF HAZARDOUS NATURE

NON-HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.

### POISONS SCHEDULE

None

### RISK

None under normal operating conditions.

### SAFETY

Do not breathe gas/fumes/vapour/spray.  
Avoid contact with skin.

---

## Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

---

NAME	CAS RN	%
paraffinic distillate, heavy, solvent- dewaxed (severe) additives nonhazardous	64742-65-0.	>60 10-30

---

## Section 4 - FIRST AID MEASURES

---

### SWALLOWED

- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.

continued...

# FOUR C FC-W 10W-40

Chemwatch Material Safety Data Sheet  
Issue Date: 8-Jun-2007  
NC317ECP

CHEMWATCH 4688-80  
Version No:1  
CD 2007/2 Page 2 of 8  
Section 4 - FIRST AID MEASURES

- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Seek medical advice.

## EYE

If this product comes in contact with the eyes:

- Wash out immediately with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- If pain persists or recurs seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

## SKIN

If skin contact occurs:

- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

## INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor.

## NOTES TO PHYSICIAN

Treat symptomatically.

- Heavy and persistent skin contamination over many years may lead to dysplastic changes.

Pre-existing skin disorders may be aggravated by exposure to this product.

- In general, emesis induction is unnecessary with high viscosity, low volatility products, i.e. most oils and greases.

- High pressure accidental injection through the skin should be assessed for possible incision, irrigation and/or debridement.

NOTE: Injuries may not seem serious at first, but within a few hours tissue may become swollen, discoloured and extremely painful with extensive subcutaneous necrosis. Product may be forced through considerable distances along tissue planes.

---

## Section 5 - FIRE FIGHTING MEASURES

---

### EXTINGUISHING MEDIA

- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog - Large fires only.

### FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- Use water delivered as a fine spray to control fire and cool adjacent area.
- Avoid spraying water onto liquid pools.
- Do not approach containers suspected to be hot.

continued...

# FOUR C FC-W 10W-40

Chemwatch Material Safety Data Sheet  
Issue Date: 8-Jun-2007  
NC317ECP

CHEMWATCH 4688-80  
Version No:1  
CD 2007/2 Page 3 of 8  
Section 5 - FIRE FIGHTING MEASURES

- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.

## FIRE/EXPLOSION HAZARD

- Combustible.
  - Slight fire hazard when exposed to heat or flame.
  - Heating may cause expansion or decomposition leading to violent rupture of containers.
  - On combustion, may emit toxic fumes of carbon monoxide (CO).
  - May emit acrid smoke.
  - Mists containing combustible materials may be explosive.
- Other combustion products include: carbon dioxide (CO<sub>2</sub>).

## FIRE INCOMPATIBILITY

Avoid contamination with strong oxidising agents as ignition may result.

HAZCHEM: None

---

## Section 6 - ACCIDENTAL RELEASE MEASURES

---

### EMERGENCY PROCEDURES

#### MINOR SPILLS

Slippery when spilt.

- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite.
- Wipe up.
- Place in a suitable labelled container for waste disposal.

#### MAJOR SPILLS

Slippery when spilt.

Remove all ignition sources.

Minor hazard.

- Clear area of personnel.
- Alert Fire Brigade and tell them location and nature of hazard.
- Control personal contact by using protective equipment as required.
- Prevent spillage from entering drains or water ways.
- Contain spill with sand, earth or vermiculite.
- Collect recoverable product into labelled containers for recycling.
- Absorb remaining product with sand, earth or vermiculite and place in appropriate containers for disposal.
- Wash area and prevent runoff into drains or waterways.
- If contamination of drains or waterways occurs, advise emergency services.

### EMERGENCY RESPONSE PLANNING GUIDELINES (ERPG)

The maximum airborne concentration below which it is believed that nearly all individuals could be exposed for up to one hour WITHOUT experiencing or developing

life-threatening health effects is:

paraffinic distillate, heavy, solvent-dewaxed (severe) 500 mg/m<sup>3</sup>

irreversible or other serious effects or symptoms which could impair an individual's ability to take protective action is:

paraffinic distillate, heavy, solvent-dewaxed (severe) 500 mg/m<sup>3</sup>

continued...

# FOUR C FC-W 10W-40

Chemwatch Material Safety Data Sheet  
Issue Date: 8-Jun-2007  
NC317ECP

CHEMWATCH 4688-80  
Version No:1  
CD 2007/2 Page 4 of 8

## Section 6 - ACCIDENTAL RELEASE MEASURES

---

other than mild, transient adverse effects without perceiving a clearly defined odour is:  
paraffinic distillate, heavy, solvent-dewaxed (severe) 300 mg/m<sup>3</sup>

The threshold concentration below which most people will experience no appreciable risk of health effects:  
paraffinic distillate, heavy, solvent-dewaxed (severe) 100 mg/m<sup>3</sup>

American Industrial Hygiene Association (AIHA)

Ingredients considered according to the following cutoffs

Very Toxic (T+)	>= 0.1%	Toxic (T)	>= 3.0%
R50	>= 0.25%	Corrosive (C)	>= 5.0%
R51	>= 2.5%		
else	>= 10%		

where percentage is percentage of ingredient found in the mixture

**Personal Protective Equipment advice is contained in Section 8 of the MSDS.**

---

## Section 7 - HANDLING AND STORAGE

---

### PROCEDURE FOR HANDLING

Remove all ignition sources.

- Limit all unnecessary personal contact.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

### SUITABLE CONTAINER

- Metal can or drum
- Packaging as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

### STORAGE INCOMPATIBILITY

Avoid storage with oxidisers.

### STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- No smoking, naked lights or ignition sources.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

continued...

# FOUR C FC-W 10W-40

Chemwatch Material Safety Data Sheet  
Issue Date: 8-Jun-2007  
NC317ECP

CHEMWATCH 4688-80  
Version No:1  
CD 2007/2 Page 5 of 8

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

### EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m <sup>3</sup>	STEL ppm	STEL mg/m <sup>3</sup>	Peak ppm	Peak mg/m <sup>3</sup>	TWA F/CC
Australia Exposure Standards	paraffinic distillate, heavy, solvent-dewaxed (severe) (Oil mist, refined mineral)		5					

### MATERIAL DATA

Not available. Refer to individual constituents.

### INGREDIENT DATA

#### PARAFFINIC DISTILLATE, HEAVY, SOLVENT-DEWAXED (SEVERE):

Human exposure to oil mist alone has not been demonstrated to cause health effects except at levels above 5 mg/m<sup>3</sup> (this applies to particulates sampled by a method that does not collect vapour). It is not advisable to apply this standard to oils containing unknown concentrations and types of additive.

### PERSONAL PROTECTION

#### EYE

- Safety glasses with side shields; or as required,
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

#### HANDS/FEET

Wear chemical protective gloves, eg. PVC.  
Wear safety footwear.

#### OTHER

- Overalls.
- Eyewash unit.

#### RESPIRATOR

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Breathing Zone Level

Maximum Protection

Half- face Respirator

Full- Face Respirator

continued...

# FOUR C FC-W 10W-40

Chemwatch Material Safety Data Sheet  
Issue Date: 8-Jun-2007  
NC317ECP

CHEMWATCH 4688-80  
Version No:1  
CD 2007/2 Page 6 of 8

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

ppm (volume)	Factor		
1000	10	A- AUS P	-
1000	50	-	A- AUS P
5000	50	Airline *	-
5000	100	-	A- 2 P
10000	100	-	A- 3 P
	100+		Airline**

\* - Continuous Flow

\*\* - Continuous-flow or positive pressure demand.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.  
For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

## ENGINEERING CONTROLS

General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas.

## Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

### APPEARANCE

Oily liquid; does not mix with water.

### PHYSICAL PROPERTIES

Liquid.

Does not mix with water.

Floats on water.

Molecular Weight: Not applicable  
Melting Range (°C): Not available  
Solubility in water (g/L): Immiscible  
pH (1% solution): Not applicable  
Volatile Component (%vol): Not available  
Relative Vapour Density (air=1): Not available  
Lower Explosive Limit (%): Not available  
Autoignition Temp (°C): Not available  
State: Liquid

Boiling Range (°C): Not available  
Specific Gravity (water= 1): <1  
pH (as supplied): Not applicable  
Vapour Pressure (kPa): Negligible  
Evaporation Rate: Not available  
Flash Point (°C): >200  
Upper Explosive Limit (%): Not available  
Decomposition Temp (°C): Not available  
Viscosity: Not Available

## Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

### CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

## Section 11 - TOXICOLOGICAL INFORMATION

### POTENTIAL HEALTH EFFECTS

continued...

# FOUR C FC-W 10W-40

Chemwatch Material Safety Data Sheet  
Issue Date: 8-Jun-2007  
NC317ECP

CHEMWATCH 4688-80  
Version No:1  
CD 2007/2 Page 7 of 8  
Section 11 - TOXICOLOGICAL INFORMATION

## ACUTE HEALTH EFFECTS

### SWALLOWED

The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. The material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.

### EYE

The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

### SKIN

The liquid may be miscible with fats or oils and may degrease the skin, producing a skin reaction described as non-allergic contact dermatitis. The material is unlikely to produce an irritant dermatitis as described in EC Directives . Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

### INHALED

Not normally a hazard due to non-volatile nature of product. Inhalation of oil droplets/ aerosols may cause discomfort and may produce chemical pneumonitis.

## CHRONIC HEALTH EFFECTS

Principal route of exposure is by skin contact; lesser exposures include inhalation of fumes from hot oils, oil mists or droplets. Prolonged contact with mineral oils carries with it the risk of skin conditions such as oil folliculitis, eczematous dermatitis, pigmentation of the face (melanosis) and warts on the sole of the foot (plantar warts). With highly refined mineral oils no appreciable systemic effects appear to result through skin absorption.

Exposure to oil mists frequently elicits respiratory conditions, such as asthma; the provoking agent is probably an additive. High oil mist concentrations may produce lipoid pneumonia although clinical evidence is equivocal. In animals exposed to concentrations of 100 mg/m<sup>3</sup> oil mist, for periods of 12 to 26 months, the activity of lung and serum alkaline phosphatase enzyme was raised; 5 mg/m<sup>3</sup> oil mist did not produce this response. These enzyme changes are sensitive early indicators of lung damage. Workers exposed to vapours of mineral oil and kerosene for 5 to 35 years showed an increased prevalence of slight basal lung fibrosis.

## TOXICITY AND IRRITATION

Not available. Refer to individual constituents.

### PARAFFINIC DISTILLATE, HEAVY, SOLVENT-DEWAXED (SEVERE):

No data of toxicological significance identified in literature search.

The substance is classified by IARC as Group 3:

NOT classifiable as to its carcinogenicity to humans.

Evidence of carcinogenicity may be inadequate or limited in animal testing.

continued...

# FOUR C FC-W 10W-40

Chemwatch Material Safety Data Sheet  
Issue Date: 8-Jun-2007  
NC317ECP

CHEMWATCH 4688-80  
Version No:1  
CD 2007/2 Page 8 of 8

---

## Section 12 - ECOLOGICAL INFORMATION

---

No data for Four C FC-W 10W-40.

---

## Section 13 - DISPOSAL CONSIDERATIONS

---

- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Authority for disposal.
- Bury or incinerate residue at an approved site.
- Recycle containers if possible, or dispose of in an authorised landfill.

---

## Section 14 - TRANSPORTATION INFORMATION

---

HAZCHEM: None

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS:UN, IATA,  
IMDG

---

## Section 15 - REGULATORY INFORMATION

---

**POISONS SCHEDULE: None**

### REGULATIONS

paraffinic distillate, heavy, solvent-dewaxed (severe) (CAS: 64742-65-0) is found on the following regulatory lists;

Australia Exposure Standards

Australia High Volume Industrial Chemical List (HVICL)

Australia Inventory of Chemical Substances (AICS)

OECD Representative List of High Production Volume (HPV) Chemicals

---

## Section 16 - OTHER INFORMATION

---

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

*This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.*

Issue Date: 8-Jun-2007

Print Date: 8-Jun-2007