

RA-SYN HIGH PERFORMANCE TWO STROKE OIL

Chemwatch Material Safety Data Sheet

Issue Date: 8-Jun-2007

NC317ECP

CHEMWATCH 4688-81

Version No:2.0

CD 2008/2 Page 1 of 13

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

RA-SYN HIGH PERFORMANCE TWO STROKE OIL

PRODUCT USE

Two stroke oil.

SUPPLIER

Company: Anglo Design

Address:

2 Beaumont Road

Mount Kuringai

NSW, 2080

AUS

Telephone: +61 2 9457 8566

Fax: +61 2 9457 8057

Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.

POISONS SCHEDULE

None

RISK

Risk Codes

R65

R66

Risk Phrases

HARMFUL - May cause lung damage if swallowed.

Repeated exposure may cause skin dryness and cracking.

SAFETY

Safety Codes

S23

S25

S36

S51

S09

S401

Safety Phrases

Do not breathe gas/ fumes/ vapour/ spray.

Avoid contact with eyes.

Wear suitable protective clothing.

Use only in well ventilated areas.

Keep container in a well ventilated place.

To clean the floor and all objects contaminated by this material use water and detergent.

S07

Keep container tightly closed.

S13

Keep away from food drink and animal feeding stuffs.

S26

In case of contact with eyes rinse with plenty of water and contact Doctor or Poisons Information Centre.

S46

If swallowed IMMEDIATELY contact Doctor or Poisons Information Centre (show this container or label).

continued...

RA-SYN HIGH PERFORMANCE TWO STROKE OIL

Chemwatch Material Safety Data Sheet

Issue Date: 8-Jun-2007

NC317ECP

CHEMWATCH 4688-81

Version No:2.0

CD 2008/2 Page 2 of 13

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
paraffinic distillate, heavy, solvent- dewaxed (severe)	64742-65-0.	30-60
kerosine, (petroleum), hydrodesulfurised	64742-81-0	10-30
ester lubricant nonhazardous		10-30
poly alpha olefin nonhazardous		10-30
performance additives nonhazardous		10-30

Section 4 - FIRST AID MEASURES

SWALLOWED

For advice, contact a Poisons Information Centre or a doctor.

- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious
- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Seek medical advice.

EYE

If this product comes in contact with the eyes:

- Wash out immediately with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- If pain persists or recurs seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

If skin contact occurs:

- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prosthesis such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor.

NOTES TO PHYSICIAN

For acute or short term repeated exposures to petroleum distillates or related hydrocarbons:

- Primary threat to life, from pure petroleum distillate ingestion and/or inhalation, is respiratory failure.
- Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO₂ 50 mm Hg) should be intubated.
- Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial injury has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.
- A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.

continued...

RA-SYN HIGH PERFORMANCE TWO STROKE OIL

Chemwatch Material Safety Data Sheet

Issue Date: 8-Jun-2007

NC317ECP

CHEMWATCH 4688-81

Version No:2.0

CD 2008/2 Page 3 of 13

Section 4 - FIRST AID MEASURES

-
- Epinephrine (adrenalin) is not recommended for treatment of bronchospasm because of potential myocardial sensitisation to catecholamines. Inhaled cardioselective bronchodilators (e.g. Alupent, Salbutamol) are the preferred agents, with aminophylline a second choice.
 - Lavage is indicated in patients who require decontamination; ensure use of cuffed endotracheal tube in adult patients. [Ellenhorn and Barceloux: Medical Toxicology].

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog - Large fires only.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- Use water delivered as a fine spray to control fire and cool adjacent area.
- Avoid spraying water onto liquid pools.
- Do not approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.

FIRE/EXPLOSION HAZARD

- Combustible.
- Slight fire hazard when exposed to heat or flame.
- Heating may cause expansion or decomposition leading to violent rupture of containers.
- On combustion, may emit toxic fumes of carbon monoxide (CO).
- May emit acrid smoke.
- Mists containing combustible materials may be explosive.

Other combustion products include: carbon dioxide (CO₂), other pyrolysis products
typical of burning organic material.

FIRE INCOMPATIBILITY

Avoid contamination with strong oxidising agents as ignition may result.

HAZCHEM: None

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

Slippery when spilt.

- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite.
- Wipe up.
- Place in a suitable labelled container for waste disposal.

continued...

RA-SYN HIGH PERFORMANCE TWO STROKE OIL

Chemwatch Material Safety Data Sheet

Issue Date: 8-Jun-2007

NC317ECP

CHEMWATCH 4688-81

Version No:2.0

CD 2008/2 Page 4 of 13

Section 6 - ACCIDENTAL RELEASE MEASURES

MAJOR SPILLS

Slippery when spilt.

Moderate hazard.

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- No smoking, naked lights or ignition sources.
- Increase ventilation.
- Stop leak if safe to do so.
- Contain spill with sand, earth or vermiculite.
- Collect recoverable product into labelled containers for recycling.
- Absorb remaining product with sand, earth or vermiculite.
- Collect solid residues and seal in labelled drums for disposal.
- Wash area and prevent runoff into drains.
- If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.
- Avoid smoking, naked lights or ignition sources.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.

SUITABLE CONTAINER

- Metal can or drum
- Packaging as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

STORAGE INCOMPATIBILITY

Avoid storage with oxidisers.

STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- No smoking, naked lights or ignition sources.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

continued...

RA-SYN HIGH PERFORMANCE TWO STROKE OIL

Chemwatch Material Safety Data Sheet

Issue Date: 8-Jun-2007

NC317ECP

CHEMWATCH 4688-81

Version No:2.0

CD 2008/2 Page 5 of 13

Section 7 - HANDLING AND STORAGE

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



+: *May be stored together*

O: *May be stored together with specific preventions*

X: *Must not be stored together*

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

The following materials had no OELs on our records

- paraffinic distillate, heavy, solvent- dewaxed (severe):
- kerosine, (petroleum), hydrodesulfurised:

CAS:64742- 65- 0

CAS:64742- 81- 0

MATERIAL DATA

Not available. Refer to individual constituents.

INGREDIENT DATA

KEROSINE, (PETROLEUM), HYDRODESULFURISED:

PARAFFINIC DISTILLATE, HEAVY, SOLVENT-DEWAXED (SEVERE):

Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations. Present day expectations require that nearly every individual should be protected against even minor sensory irritation and exposure standards are established using uncertainty factors or safety factors of 5 to 10 or more. On occasion animal no-observable-effect-levels (NOEL) are used to determine these limits where human results are unavailable. An additional approach, typically used by the TLV committee (USA) in determining respiratory standards for this group of chemicals, has been to assign ceiling values (TLV C) to rapidly acting irritants and to assign short-term exposure limits (TLV STELs) when the weight of evidence from irritation, bioaccumulation and other endpoints combine to warrant such a limit. In contrast the MAK Commission (Germany) uses a five-category system based on intensive odour, local irritation, and elimination half-life. However this system is being replaced to be consistent with the European Union (EU) Scientific Committee for Occupational Exposure Limits (SCOEL); this is more closely allied to that of the USA.

OSHA (USA) concluded that exposure to sensory irritants can:

- cause inflammation
- cause increased susceptibility to other irritants and infectious agents
- lead to permanent injury or dysfunction
- permit greater absorption of hazardous substances and
- acclimate the worker to the irritant warning properties of these substances thus increasing the risk of overexposure.

PARAFFINIC DISTILLATE, HEAVY, SOLVENT-DEWAXED (SEVERE):

NOTE L: The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3% DMSO extract as measured by IP 346. European Union (EU) List of Dangerous Substances (Annex I) - up to the 29th ATP.

ES TWA: 5 mg/m³ refined mineral oil mist.

Human exposure to oil mist alone has not been demonstrated to cause health effects

continued...

RA-SYN HIGH PERFORMANCE TWO STROKE OIL

Chemwatch Material Safety Data Sheet

Issue Date: 8-Jun-2007

NC317ECP

CHEMWATCH 4688-81

Version No:2.0

CD 2008/2 Page 6 of 13

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

except at levels above 5 mg/m³ (this applies to particulates sampled by a method that does not collect vapour). It is not advisable to apply this standard to oils containing unknown concentrations and types of additive.

KEROSENE, (PETROLEUM), HYDRODESULFURISED:

Exposure limits with "skin" notation indicate that vapour and liquid may be absorbed through intact skin. Absorption by skin may readily exceed vapour inhalation exposure. Symptoms for skin absorption are the same as for inhalation. Contact with eyes and mucous membranes may also contribute to overall exposure and may also invalidate the exposure standard.

CAUTION: This substance has been classified by the ACGIH as A3 Animal Carcinogen (at relatively high doses).

for kerosene CAS 8008-20-6

TLV TWA: 200 mg/m³ as total hydrocarbon vapour Skin A3

OEL TWA: 14 ppm, 100 mg/m³

REL TWA: 150 ppm

CEL TWA: 300 ppm, 900 mg/m³

[NIOSH, 1985]
[Shell]

PERSONAL PROTECTION



EYE

- Safety glasses with side shields; or as required,
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

- Barrier cream with polyethylene gloves. or - Nitrile rubber gloves.
- Wear chemical protective gloves, eg. PVC.
- Wear safety footwear.

OTHER

- Overalls.
- Eyewash unit.

RESPIRATOR

Respiratory protection may be required when ANY "Worst Case" vapour-phase concentration is exceeded (see Computer Prediction in "Exposure Standards")

Protection Factor (Min)	Half- Face Respirator	Full- Face Respirator
10 x ES	Air- line*	A- P- - 2
	-	A- P- - PAPP- 2

continued...

RA-SYN HIGH PERFORMANCE TWO STROKE OIL

Chemwatch Material Safety Data Sheet

Issue Date: 8-Jun-2007

NC317ECP

CHEMWATCH 4688-81

Version No:2.0

CD 2008/2 Page 7 of 13

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

20 x ES	-	A- P- - 3
20+ x ES	-	Air- line**

* - Continuous-flow; ** - Continuous-flow or positive pressure demand

^ - Full-face.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required. For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

Use in a well-ventilated area.

General exhaust is adequate under normal operating conditions. Local exhaust ventilation may be required in specific circumstances. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Oily liquid with hydrocarbon solvent odour; does not mix with water.

PHYSICAL PROPERTIES

Liquid.

Does not mix with water.

Floats on water.

Molecular Weight: Not applicable
Melting Range (°C): Not available
Solubility in water (g/L): Immiscible
pH (1% solution): Not applicable
Volatile Component (%vol): Not available
Relative Vapour Density (air=1): >1
Lower Explosive Limit (%): Not Available
Autoignition Temp (°C): Not Available
State: Liquid

Boiling Range (°C): Not Available
Specific Gravity (water= 1): <1
pH (as supplied): Not applicable
Vapour Pressure (kPa): Not Available
Evaporation Rate: Not available
Flash Point (°C): Not Available
Upper Explosive Limit (%): Not Available
Decomposition Temp (°C): Not available
Viscosity: Not Available

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

Accidental ingestion of the material may be damaging to the health of the individual.

Ingestion may result in nausea, pain, vomiting. Vomit entering the lungs by aspiration may cause

continued...

RA-SYN HIGH PERFORMANCE TWO STROKE OIL

Chemwatch Material Safety Data Sheet

Issue Date: 8-Jun-2007

NC317ECP

CHEMWATCH 4688-81

Version No:2.0

CD 2008/2 Page 8 of 13

Section 11 - TOXICOLOGICAL INFORMATION

potentially lethal chemical pneumonitis.

EYE

There is some evidence to suggest that this material can cause eye irritation and damage in some persons.

SKIN

Skin contact with the material may damage the health of the individual; systemic effects may result following absorption.
The liquid may produce skin discomfort following prolonged contact. Defatting and/or drying of the skin may lead to dermatitis.
The material may accentuate any pre-existing skin condition.

INHALED

Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination.

CHRONIC HEALTH EFFECTS

Chronic solvent inhalation exposures may result in nervous system impairment and liver and blood changes. [PATTYS].

Constant or exposure over long periods to mixed hydrocarbons may produce stupor with dizziness, weakness and visual disturbance, weight loss and anaemia, and reduced liver and kidney function. Skin exposure may result in drying and cracking and redness of the skin. Chronic exposure to lighter hydrocarbons can cause nerve damage, peripheral neuropathy, bone marrow dysfunction and psychiatric disorders as well as damage the liver and kidneys.

TOXICITY AND IRRITATION

Not available. Refer to individual constituents.

PARAFFINIC DISTILLATE, HEAVY, SOLVENT-DEWAXED (SEVERE):
unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

No data of toxicological significance identified in literature search.

The substance is classified by IARC as Group 3:

NOT classifiable as to its carcinogenicity to humans.

Evidence of carcinogenicity may be inadequate or limited in animal testing.

KEROSINE, (PETROLEUM), HYDRODESULFURISED:
unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (rat) LD50: >5000 mg/kg

Inhalation (rat) LC50: >5000 mg/m³/4h

Dermal (rabbit) LD50: >2000 mg/kg

The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

IRRITATION

Skin (rabbit): 500 mg/24h - Moderate

MATERIAL	CARCINOGEN	REPROTOXIN	SENSITISER	SKIN
paraffinic distillate, heavy, solvent- dewaxed (severe)	IARC:3			

CARCINOGEN

IARC: International Agency for Research on Cancer (IARC) Carcinogens: paraffinic distillate, heavy, solvent-dewaxed (severe) Category: The substance is classified by IARC as Group 3: NOT classifiable as to its carcinogenicity to humans. Evidence of

continued...

RA-SYN HIGH PERFORMANCE TWO STROKE OIL

Chemwatch Material Safety Data Sheet

Issue Date: 8-Jun-2007

NC317ECP

CHEMWATCH 4688-81

Version No:2.0

CD 2008/2 Page 9 of 13

Section 11 - TOXICOLOGICAL INFORMATION

carcinogenicity may be inadequate or limited in animal testing.

Section 12 - ECOLOGICAL INFORMATION

The lower molecular weight hydrocarbons are expected to form a "slick" on the surface of waters after release in calm sea conditions. This is expected to evaporate and enter the atmosphere where it will be degraded through reaction with hydroxy radicals.

Some of the material will become associated with benthic sediments, and it is likely to be spread over a fairly wide area of sea floor. Marine sediments may be either aerobic or anaerobic. The material, in probability, is biodegradable, under aerobic conditions (isomerised olefins and alkenes show variable results). Evidence also suggests that the hydrocarbons may be degradable under anaerobic conditions although such degradation in benthic sediments may be a relatively slow process.

Under aerobic conditions the material will degrade to water and carbon dioxide, while under anaerobic processes it will produce water, methane and carbon dioxide.

Based on test results, as well as theoretical considerations, the potential for bioaccumulation may be high. Toxic effects are often observed in species such as blue mussel, daphnia, freshwater green algae, marine copepods and amphipods.

Drinking Water Standards: hydrocarbon total: 10 ug/l (UK max.).

DO NOT discharge into sewer or waterways.

Refer to data for ingredients, which follows:

PARAFFINIC DISTILLATE, HEAVY, SOLVENT-DEWAXED (SEVERE):

DO NOT discharge into sewer or waterways.

KEROSINE, (PETROLEUM), HYDRODESULFURISED:

The lower molecular weight hydrocarbons are expected to form a "slick" on the surface of waters after release in calm sea conditions. This is expected to evaporate and enter the atmosphere where it will be degraded through reaction with hydroxy radicals.

Some of the material will become associated with benthic sediments, and it is likely to be spread over a fairly wide area of sea floor. Marine sediments may be either aerobic or anaerobic. The material, in probability, is biodegradable, under aerobic conditions (isomerised olefins and alkenes show variable results). Evidence also suggests that the hydrocarbons may be degradable under anaerobic conditions although such degradation in benthic sediments may be a relatively slow process.

Under aerobic conditions the material will degrade to water and carbon dioxide, while under anaerobic processes it will produce water, methane and carbon dioxide.

Based on test results, as well as theoretical considerations, the potential for bioaccumulation may be high. Toxic effects are often observed in species such as blue mussel, daphnia, freshwater green algae, marine copepods and amphipods.

Drinking Water Standards: hydrocarbon total: 10 ug/l (UK max.).

DO NOT discharge into sewer or waterways.

for gas oils and distillate fuels:

The gas oils category includes both finished products (distillate fuels) and the refinery streams (gas oils) from which they are blended. The materials in this category, together with those in the Jet Fuel/Kerosene category, constitute a generic class of petroleum substances commonly known as middle distillates. The distillate fuels covered in this category are used in diesel engines and for both industrial and domestic heating. While within the refinery the gas oil streams exist primarily as intermediates in closed systems. Selected gas oil streams may ultimately be blended into distillate fuels, marine bunker fuels and occasionally into lubricants. At ambient temperatures, all the substances in this category are liquids. Gas oil streams and distillate fuels are complex

continued...

RA-SYN HIGH PERFORMANCE TWO STROKE OIL

Chemwatch Material Safety Data Sheet

Issue Date: 8-Jun-2007

NC317ECP

CHEMWATCH 4688-81

Version No:2.0

CD 2008/2 Page 10 of 13

Section 12 - ECOLOGICAL INFORMATION

petroleum mixtures, composed primarily of saturated (paraffinic and naphthenic) or aromatic hydrocarbons with carbon numbers ranging from C9 to C30.

Gas Oils are similar from both a process and physical-chemical perspective, being differentiated from each other primarily by their aromatic and saturated hydrocarbon content. The compositions of the gas oil streams range from those that are predominantly saturated hydrocarbons to those that are predominantly aromatic hydrocarbons.

Consequently, the category can be considered a continuum, bounded by materials that are compositionally either high in saturated hydrocarbons or aromatic hydrocarbons. While the ratio of the saturated and aromatic hydrocarbons may vary between category members the saturated and aromatic hydrocarbons species that make up the category members are similar. Based on the available data, the physical-chemical properties of an individual category member depend on its compositional makeup, vis a vis saturated and aromatic hydrocarbons. Therefore, gas oil streams that are predominantly saturated hydrocarbons will have similar physical-chemical properties, while those that are composed predominantly of aromatic hydrocarbons will have somewhat different properties. As products that are blended from the gas oil streams, the compositions of the distillate fuels fall within the range of the compositions shown by the gas oil streams and reflect the characteristics of the gas oils streams from which they are blended.

Boiling Point Gas oils do not have a single numerical value for boiling point, but rather a boiling or distillation range that reflects the individual components in the hydrocarbon mixture. Distillation ranges for a variety of gas oils have been reported for a number of blended gas oil products and individual gas oil production streams. Typical distillation ranges for blended fuels are 160 to 390 C for an automotive gas oil (diesel fuel), 160 to 400 C for a heating oil, and 170 to 420 C for a distillate marine fuel. Typical low end and high end distillation temperatures for gas oil production streams were 172 and 344 C for a hydrodesulfurised middle distillate (65.6% -79.4% saturated hydrocarbons), 185 and 391 C for a straight-run middle distillate (78.8 saturated hydrocarbons), and 185 and 372 C for a light catalytic cracked distillate (60.8% -79.8% aromatic hydrocarbons). No substantial differences in boiling range were apparent for gas oils with high concentrations of either aromatic or saturated hydrocarbons.

Vapor Pressure : For mixtures such as petroleum products, the vapor pressure of the mixture is the sum of the partial pressures of the individual components (Dalton's Law of Partial Pressures). Gas oils are expected to have low vapor pressure due to their boiling range (150 to 450 C) and molecular weights of the constituent hydrocarbons (C9 – 30 carbon atoms). Because the physical-chemical characteristics of distillate fuels reflect the gas oil streams from which they were produced, these vapor pressure measurements are expected to approximate the vapor pressures of individual gas oils. Vapour pressure estimates of low molecular weight hydrocarbons of varying isomeric structures fell within a range of 0.01 to 1.6 kPa, with higher molecular weight hydrocarbons showing very low vapour pressures (e.g., 10⁻⁸ to 10⁻¹⁰ kPa).

Partition Coefficient The percent distribution of the hydrocarbon groups (i.e., paraffins, olefins, naphthenes, and aromatics) and the carbon chain lengths of hydrocarbon constituents in gas oils largely determines the partitioning characteristics of the mixture. Generally, hydrocarbon chains with fewer carbon atoms tend to have lower partition coefficients than those with higher carbon numbers. Because gas oils are complex mixtures, it is not possible to determine their log Kow values. Rather, partition coefficients have been calculated for individual component hydrocarbons from known hydrocarbon composition. Those calculated Kow values ranged from 3.9 to >6.0 for a hydrodesulfurized middle distillate ((65.6% -79.4% saturated hydrocarbons), straight-run middle distillate (78.8% saturated hydrocarbons), and a light cat-cracked distillate (60.8% -79.8% aromatic hydrocarbons). There are no apparent differences in the range of Kow values determined for gas oils with high concentrations of either aromatic or saturated hydrocarbons. A similar range of partition coefficients would be expected for component hydrocarbons in distillate fuels.

Environmental fate:

Photodegradation : The direct aqueous photolysis of an organic molecule occurs when it absorbs sufficient light energy to result in a structural transformation. Only light energy at wavelengths between 290 and 750 nm can result in photochemical transformations in the environment, although absorption is not always sufficient for a chemical to

continued...

RA-SYN HIGH PERFORMANCE TWO STROKE OIL

Chemwatch Material Safety Data Sheet

Issue Date: 8-Jun-2007

NC317ECP

CHEMWATCH 4688-81

Version No:2.0

CD 2008/2 Page 11 of 13

Section 12 - ECOLOGICAL INFORMATION

undergo photochemical degradation. Saturated and one-ring aromatic hydrocarbons do not show absorbance in the 290 to 800 nm range and would not be expected to be directly photodegraded. Polyaromatic hydrocarbons, on the other hand, have shown absorbance of the 290 to 800 nm range of light energy and could potentially undergo photolysis reactions. The degree and rate at which these compounds photodegrade depends upon whether conditions allow penetration of light with sufficient energy to effect a change.

Components in gas oils that do not directly photodegrade (e.g., paraffins, naphthenes, and one-ring aromatic compounds) may be subject to indirect photodegradation. Indirect photodegradation is the reaction with photosensitised oxygen in the atmosphere in the form of hydroxyl radicals (OH).

Atmospheric oxidation rates and half-lives were calculated for the low and high end of the range of molecular weight constituents of gas oils (e.g., C9 and C30 hydrocarbon structures). Half-life estimates for these compounds ranged from 0.1 (for various C9 to C30 olefinic structures and C30 2+ring aromatic compounds) to 1.5 days (for a C9 one-ring aromatic structure). Based on the calculated half-life values calculated

no substantial

differences in indirect photodegradation potential is expected between gas oils with high concentrations of either aromatic or saturated hydrocarbons. A similar range of water solubility values would be expected for component hydrocarbons in distillate fuels.

Water Solubility : When released to water, gas oils will float and spread at a rate that is viscosity-dependent. Component hydrocarbons in gas oils will partition to water according to their individual solubility values. For individual hydrocarbon constituents in gas oils, water solubility values vary by orders of magnitude. Molecular weight and chemical structure have a great influence on the ultimate degree of solubility.

Calculated water solubility ranged from essentially insoluble (approximately 10-8 mg/L) for the higher molecular weight fractions (e.g., C30) within gas oil to approximately 52 mg/L for a C9 alkylbenzene.

Hydrolysis: The materials in the gas oils category do not contain chemical moieties that undergo hydrolysis.

Transport and Distribution in the Environment (Fugacity) Models have been used to estimate the percent distribution in environmental media (i.e., air, water, soil, sediment, and fish) of various C9 to C30 compounds representing the different classes of hydrocarbons found in gas oils (e.g., paraffins, olefins, naphthenes, and aromatics).

Hydrocarbons having nine carbon atoms showed a tendency to partition to air (up to 98%). As molecular weight increases, partitioning shifts to soil, which accounts for 98% of the distribution of the C30 components. This trend was similar for saturate and aromatic structures alike. Therefore, gas oils with high concentrations of either aromatic or saturated hydrocarbons are expected to partition in the environment in a similar manner

Biodegradation : Much of what is known is based on information gained from testing hydrocarbon mixtures of other petroleum products. Under standard biodegradability tests, hydrocarbon compounds representative of those found in gas oils typically do not pass ready biodegradability test conditions. Although those compounds are not recognized as being readily biodegradable, most hydrocarbon species present in gas oils are known to be ultimately degraded by aerobic microorganisms

Lower molecular weight compounds may be expected to be degraded relatively quickly in aerobic conditions, while higher molecular weight compounds, particularly polycyclic aromatics, will degrade slower. Much of this evidence is based on bioremediation studies of contaminated soils, which have shown that hydrocarbon components in gas oils are degraded in the presence of oxygen. Bioremediation of a diesel fuel spill has also been demonstrated under Arctic conditions

Under anaerobic conditions, such as anoxic sediments, rates of biodegradation of gas oils components are negligible and the gas oils may persist under those conditions for some time. Degradation then will be dependent on bioturbation or resuspension to provide microbes with access to oxygen.

Ecotoxicity:

Multiple ecotoxicological studies on heating and transportation fuels (e.g., no. 2 fuel oil and diesel fuel) have been conducted. In general, these commercial distillate fuels show moderate toxicity to aquatic life. LC50 values for fish ranged from 3.2 to 65 mg/L, while EC50 values for invertebrates ranged from 2.0 to 210 mg/L.

continued...

RA-SYN HIGH PERFORMANCE TWO STROKE OIL

Chemwatch Material Safety Data Sheet

Issue Date: 8-Jun-2007

NC317ECP

CHEMWATCH 4688-81

Version No:2.0

CD 2008/2 Page 12 of 13

Section 13 - DISPOSAL CONSIDERATIONS

- Consult manufacturer for recycling options and recycle where possible .
- Consult State Land Waste Management Authority for disposal.
- Incinerate residue at an approved site.
- Recycle containers if possible, or dispose of in an authorised landfill.

Section 14 - TRANSPORTATION INFORMATION

HAZCHEM: None

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: UN, IATA, IMDG

Section 15 - REGULATORY INFORMATION

POISONS SCHEDULE: None

REGULATIONS

Ra-Syn High Performance Two Stroke Oil (CAS: None):
No regulations applicable

paraffinic distillate, heavy, solvent-dewaxed (severe) (CAS: 64742-65-0) is found on the following regulatory lists:

- Australia Hazardous Substances
- Australia High Volume Industrial Chemical List (HVICL)
- Australia Inventory of Chemical Substances (AICS)
- International Agency for Research on Cancer (IARC) Carcinogens
- OECD Representative List of High Production Volume (HPV) Chemicals

kerosine, (petroleum), hydrodesulfurised (CAS: 64742-81-0) is found on the following regulatory lists:

- Australia Hazardous Substances
- Australia High Volume Industrial Chemical List (HVICL)
- Australia Inventory of Chemical Substances (AICS)
- Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Schedule 5
- International Air Transport Association (IATA) Dangerous Goods Regulations
- International Council of Chemical Associations (ICCA) - High Production Volume List
- OECD Representative List of High Production Volume (HPV) Chemicals
- OSPAR List of Chemicals for Priority Action

Section 16 - OTHER INFORMATION

EXPOSURE STANDARD FOR MIXTURES

"Worst Case" computer-aided prediction of vapour components/concentrations:

Composite Exposure Standard for Mixture (TWA) (mg/m³): 900 mg/m³

If the breathing zone concentration of ANY of the components listed below is exceeded,

"Worst Case" considerations deem the individual to be overexposed.

Component Breathing Zone ppm Breathing Zone mg/m³ Mixture Conc: (%)

Component	Breathing zone (ppm)	Breathing Zone (mg/m ³)	Mixture Conc (%)
kerosine, (petroleum), hydrodesulfurised	300.00	900.0000	30.0

Operations which produce a spray/mist or fume/dust, introduce particulates to the breathing zone.

If the breathing zone concentration of ANY of the components listed below is exceeded,

"Worst Case" considerations deem the individual to be overexposed.

At the "Composite Exposure Standard for Mixture" (TWA) (mg/m³): 900 mg/m³

Classification of the preparation and its individual components has drawn on official and

continued...

RA-SYN HIGH PERFORMANCE TWO STROKE OIL

Chemwatch Material Safety Data Sheet

Issue Date: 8-Jun-2007

NC317ECP

CHEMWATCH 4688-81

Version No:2.0

CD 2008/2 Page 13 of 13

Section 16 - OTHER INFORMATION

authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net/references.

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 8-Jun-2007

Print Date: 5-Sep-2008