

## Product Description

**Anglomoil Multitrac Super** is a multi-functional STOU (Super Tractor Oil Universal) lubricant suitable for a wide range of agricultural machines from compressors to combine harvesters.

## Product Features & Benefits

**Anglomoil Multitrac Super** is a multipurpose lubricant for Crankcase of diesel and four stroke gasoline engines, transmissions, hydraulics, power take offs, wet brakes, hydrostatics and power steering. of a wide range of agricultural and industrial tractors and implements.

**Anglomoil Multitrac Super** will meet the performance requirements

- of Massey Ferguson M1143 but can not be claimed as it is a UTTO specification only and not applicable to STOU fluids.
- API CI-4 and ACEA E7 level of soot control
- ACEA E4-08 and MB228.3 level of wear performance on B05 fuel.
- MB-Approval 228.3 and ACEA E7 level of piston cleanliness on B05 fuel.

## Additional Information

**Anglomoil Multitrac Super** is the one fluid to lubricate the entire tractor. It is a STOU (Super Tractor Oil Universal) and as it is the only lubricant required it eliminates the chances for misapplication.

**Anglomoil Multitrac Super** provides:

- Superior soot handling
- Excellent antiwear to prolong the life of your equipment
- Thermal and oxidative stability to reduce thickening of the oil which otherwise leads to reduced lubrication and increased wear
- Excellent acid neutralization to prevent engine corrosion and improve durability.
- Reduced friction which assists at startup to reduce wear.
- Water protection to make sure that the engine and components are properly lubricated at all times.

## Performance Levels

**Anglomoil Multitrac Super** meets or exceeds the performance of:

<b>Agricultural and Off Highway</b>	John Deere JDM J27	Allison C-4	ZF TE-ML 06B
	Massey Ferguson CMS M1145	API GL-4	ZF TE-ML 06C
	Massey Ferguson CMS M1144	Ford M2C159-B	ZF TE-ML 06D
	Massey Ferguson CMS M1139	Caterpillar TO-2	ZF TE-ML 07B
<b>Engine Performance</b>	ACEA E2	API SF	MAN 271
	API CE	MB-Approval 227.1	MIL-L-2104D
	API CF	MB-Approval 228.1	
	API CF-4	MB-Approval 228.3	

## Typical Characteristics

Physical Properties		Chemical Properties	
S.G @20°C	0.889	Sulphated Ash %Wt	1.55
KV @40°C	87.8cSt	Base No. mg KOH/gm	10.4
KV @100°C	12.9cSt		
VI	146		

### Anglomoil Superior Lubricants

Lubricants for Automotive - Industry - Food - Farm Machinery - Marine - Earthmovers - Road Transport

2 Beaumont Rd, Mt Kuringai, NSW, Australia Phone: +61 2 9457 8566, Fax: +61 2 9457 8057 Email: info@anglomoil.com Web: www.anglomoil.com