



Rock Drill Oil

Available in ISO 100 & 320

Product Description

Anglomoil Rock Drill Oils are blended from selected mineral oils specially compounded to provide good lubricity, inhibit corrosion as well as emulsifiers and tack additives.

Product Applications

Mining, quarrying, construction, roadworks, tunnelling and excavations.

Caution: There have been cases where combustion of lubricant has occurred in the air chambers of some types of percussive air tools. Anglomoil strongly recommends that users do not deviate from the lubrication recommendations and guidelines provided by air tool manufacturers. Prior to any work being undertaken in areas where sources of ignition could create a high level of risk (eg. underground coal mining), a full risk assessment must be carried out to ensure that the right tools and procedures are used for the application.

Product Features & Benefits

Design features and benefits of the Anglomoil range of rock drill oils include:

High film strength.

Reduced wear allowing for operation in extremes of high or low temperatures.

Reduced friction which helps to maintain operating speed.

Ability to absorb excess water and form an emulsion when moist air is present in the system.

Improved protection against wear caused by poor lubrication.

Anglomoil Rock Drill Oil will adhere to the metal surfaces and resist blow-off.

Performance Level

The correct viscosity grade of **Anglomoil Rock Drill Oil** should be selected to suit the equipment being used and the local site operating conditions. The machinery manufacturer will usually include a selection chart in the machinery handbook to assist in the selection of the correct grade.

Typical Characteristics

Anglomoil Rock Drill Oils are available in ISO 100 & 320 viscosity grades
Due to the levels of tackifier in these oils, they have a sticky consistency.

PRODUCT DATA SHEET

Anglomoil Superior Lubricants

Lubricants for Automotive - Industry - Food - Farm Machinery - Marine - Earthmovers - Road Transport

2 Beaumont Rd, Mt Kuringai, NSW, Australia Phone: +61 2 9457 8566, Fax: +61 2 9457 8057 Email: info@anglomoil.com Web: www.anglomoil.com

Date Published : 15/09/10