

## Product Description

Anglomoil Slideway Oil series are high performance, ashless slideway lubricants based on solvent refined mineral oils.

## Product Features & Benefits

Anglomoil Slideway Oil's utilise the proven technology in lubricity, extreme pressure and demulsibility to provide optimum performance in use. They have:

- Strong demulsibility and water separation performance
- Proven stick slip performance which is required for repeatable machining.
- Exceptional anti-staining and anti-corrosion properties
- Light colour and low odour
- Excellent anti-wear and extreme pressure performance
- Non-corrosive to both ferrous and non-ferrous alloys.
- Excellent filterability
- Compatibility with commonly used cutting fluids

## Additional Information

Anglomoil Slideway Oils

- are recommended for both vertical and horizontal slideways where high quality demulsifying slideway lubricants are required.
- Can be used for both metal and plastic slideways.
- Contains **TEFLON** which enhances the fluids **load carrying** capacity providing for a **quieter operation, reduced friction and less wear.**

## Typical Characteristics

Test	Test Method	32T	68T	220T
<b>Physical Properties</b>				
Density @20°C	IP 160	0.870	0.878	0.893
KV @ 40°C	ASTM D445	36.5 cSt	72.5 cSt	214 cSt
KV @100°C	ASTM D445	6.1 cSt	9.5 cSt	19.2 cSt
VI	IP 226	114	109	101

## Performance Levels :

Anglomoil Slideway Oils meet all the requirements for

<b>Slideway Lubricant</b>	Cincinnati Lamb P-47
<b>Hydraulic and Industrial Gear Oil</b>	DIN 51524-2 HLP DIN 51517-3 CLP
<b>Additional Performance</b>	Bijur Filtration Testing SKC Coolant Separability Darmstadt Test Protocols

### Anglomoil Superior Lubricants

Lubricants for Automotive - Industry - Food - Farm Machinery - Marine - Earthmovers - Road Transport

2 Beaumont Rd, Mt Kuringai, NSW, Australia Phone: +61 2 9457 8566, Fax: +61 2 9457 8057 Email: info@anglomoil.com Web: www.anglomoil.com