

Product Description

Anglomoil Super 60 is a multigrade high viscosity engine oil with high detergency and load carrying capacity which will maintain engine cleanliness and reduce wear.

Product Features & Benefits

The very high viscosity of **Super 60** exceeds the upper limits of SAE 60 and maintains a thick film of protective oil in the load bearing components of the engine.

All petrol engine vehicles sold in Australia since 1985 are fitted with catalytic converters to clean up the exhaust gases. The phosphorus content of Roadmaster 200 is controlled to avoid any possibility of poisoning the catalyst.

Additional Information

Anglomoil Super 60 is blended from high quality base oils fortified with a balanced additive package to provide a high level of engine protection against engine sludge, varnish deposits and wear. A particular feature of the Super 60 specification is the special attention given to the reduction in wear in the valve train mechanism - and increased resistance to oil oxidation.

Typical Characteristics

| Physical Properties | | Chemical Properties | |
|---------------------|-------|---------------------|-------|
| S.G @20°C | 0.896 | Sulphated Ash %Wt | 0.84 |
| KV @40°C | 330 | Base No. mg KOH/gm | 7.5 |
| KV @100°C | 28.0 | Phosphorus %Wt | 0.085 |
| VI | 115 | | |

Performance Levels

| National | | |
|------------|-----------|-----------|
| - USA | API SL/CF | API SJ/CF |
| - European | ACEA A2 | |
| | | |

Anglomoil Superior Lubricants

Lubricants for Automotive - Industry - Food - Farm Machinery - Marine - Earthmovers - Road Transport

2 Beaumont Rd, Mt Kuringai, NSW, Australia Phone: +61 2 9457 8566, Fax: +61 2 9457 8057 Email: info@anglomoil.com Web: www.anglomoil.com