

Wire Rope-Cable Lubricant

WRL is a high viscosity, high temperature, wire rope-cable lubricant which provides excellent protection against corrosion and wear. This product protects against water wash-out and provides long lasting corrosion protection in the most harsh environments. In addition, WRL will protect against wear and abrasion. WRL has excellent adhesion to metal surfaces and is formulated for application in centralized lubrication equipment. Due to its high dropping point, WRL continues to protect in high temperatures and will not soften and run-out. This product seals out contaminants as it lubricates and provides long term protection. Also suitable for open gear applications.

PRODUCT DATA SHEET

<u>TEST</u>	<u>SPECIFICATIONS</u>
NLGI Grade	#0
Color	Black
Texture	Smooth / Tacky
Penetration, ASTM D-217 Worked 60 Strokes	355-385
Dropping Point, ASTM D-2265, °F	550°F
Timken O.K. Load, ASTM D-2509.Lbs	60
4 Ball Wear Test, mm scar ASTM D-2266	0.39
Corrosion, Salt Fog Test, ASTM B-117	2500 Hours+
Bearing Corrosion, ASTM D-1743	1,1,1
Copper Corrosion, ASTM D-4048	1b Max
Base Fluid Viscosities	
cSt @ 40°C	1154
cSt @ 100°C	66
SUS @ 100°F	6213
SUS @ 210°F	319

Anglomoil Superior Lubricants

Lubricants for Automotive - Industry - Food - Farm Machinery - Marine - Earthmovers - Road Transport

2 Beaumont Rd, Mt Kuringai, NSW, Australia Phone: +61 2 9457 8566, Fax: +61 2 9457 8057 Email: info@anglomoil.com Web: www.anglomoil.com