

## Product Description

Anglomoil Chain Oil is a premium chain oil made with mineral oils, friction modifiers, anti-wear additives and tackifier. It is a high performance product suitable for chains and bars of power chain saws.

## Recommended Applications:

- All chains, including oil baths, hand and automatic lubricated
- Bars and chains of high performance professional power chain saws
- Conveyor systems,

## Advantages:

- Additive system protects the chain, bar and sprockets from wear
- Tacky nature reduces fling-off from the chain
- Green colour helps distinguish this chain oil from engine oils
- Rust Inhibited

## Application of Oil to Industrial Applications

It is essential that lubricant reaches the bearing area of the chain by directing it into the clearances between the inner and outer link plates.

Application method	Power & Speed
Manual	Low
Drip Feed	To 37 kW @ 6 m/s
Oil Bath	To 37 kW @ 10 m/s
Pump & Sump	Drives over 37 kW

## Ambient Temperature

°C	SAE Grade
-5 to + 25	30
25 – 45	40
45 - 65	50

## Properties

Properties		
Viscosity	@ 40 deg C	126
	@ 100 deg C	14
Viscosity Index		107
Density	@ 20 deg C	0.884
SAE Viscosity	SAE	30

### Anglomoil Superior Lubricants

Lubricants for Automotive - Industry - Food - Farm Machinery - Marine - Earthmovers - Road Transport

2 Beaumont Rd, Mt Kuringai, NSW, Australia Phone: +61 2 9457 8566, Fax: +61 2 9457 8057 Email: info@anglomoil.com Web: www.anglomoil.com