

	Density @20°C	KV _{40°C}	KV _{100°C}	API	SAE	DAF	IVECO	Eaton	Renault	MAN	Scania	Volvo	ZF	Avin Meritor	International	Mack	MB	US Military	Spicer	Holden	Ford	Dana	Dana Chrysler	BTR		
Gear Oils																										
Euro Trans 75W/80	0.855	63.0	10.6	GL-4		Yes	Yes	300,000km Extended Drain	Yes	341 E-3 341 Z-3		97305-80														
Gear 50-S RoadRanger	0.860	132.0	17.5	MT-1				PS-164 rev 7					Freedomline Eurotronic 2	O-81 Pending	TMS 6816	TO-A Plus										
SYN EP 75W90	0.864	108.9	16.5	GL-4, GL-5, MT-1	J2360	Yes	Yes	Europe		3343S	STO 1:0		TE-ML-02B, 05B, 07A, 08, 12B, 16F, 17B & 19C.	0-76-N		GO-J	MB 235.8	MIL-L-2105D MIL-PRF-2105E								
SYN LS 80W140	0.884	214.8	27.7	GL-5, GL-6	J2360													MIL-L-2105D MIL-PRF-2105E	5M-48	HN-2040 HN-1561	M2C-119A M2C-104					
TRANS 90 GL1 (RM300/50)	0.894	215.0	19.8	GL-1, CF, CF-2																HN-1223 Non EP	M2C-85A					
TRANS EP 90	0.898	225.6	19.7	GL-5, MT-1	J2360					342 Type M-2	STO 1:0		TE-ML-05A, 07A, 16B, 16C, 16D, 17B & 19B.			GO-J		MIL-PRF-2105E								
TRANS EP 140	0.910	413.6	36.1	GL-5, MT-1	J2360					342 Type M-2	STO 1:0		TE-ML-05A, 07A, 16B, 16C, 16D, 17B & 19B.			GO-J		MIL-PRF-2105E								
TRANS EP 75W90	0.894	215.5	17.1	GL-4, GL-5, MT-1	J2360	Yes	Yes			M 3343 Type M	STO 1:0		TE-ML-02B, 05A, 07A, 08, 12E, 16B, 16C, 16D, 17B & 19B.	0-76-N		GO-J	MB 235.0	MIL-PRF-2105E								
TRANS EP 80W90	0.898	180.4	17.0	GL-5, MT-1	J2360					342 Type M-2	STO 1:0		TE-ML-05A, 07A, 16B, 16C, 16D, 17B & 19B.			GO-J		MIL-PRF-2105E								
TRANS EP 85W140	0.901	352.5	26.5	GL-5, MT-1	J2360					342 Type M-2	STO 1:0		TE-ML-05A, 07A, 16B, 16C, 16D, 17B & 19B.			GO-J		MIL-PRF-2105E								
TRANS LS 90	0.901	195.0	18.0	GL-5, GL-6, MT-1	J2360									Avin Meritor Axles			GO-J	MIL-PRF-2105E		HN-1561, HN-1187, HN-1386	M22C-118A	40819	MS 5630	5M-31 5M-41		
TRANS LS 140	0.900	422.0	30.0	GL-5, GL-6, MT-1	J2360									Avin Meritor Axles			GO-J	MIL-PRF-2105E		HN-1561, HN-1187, HN-1386	M22C-118A	40819	MS 5630	5M-31 5M-41		
TRANSAXLE 80W90	0.896	103.8	14.3	GL-5, MT-1	J2360					342 Type M-2	STO 1:0		TE-ML-05A, 07A, 08, 12E, 16B, 16C, 16D, 17B, 19B & 21A.				MB 235.20									

Product Description	Density @20°C	KV _{40°C}	KV _{100°C}	Viscosity	Boron ppm	Calcium ppm	Magnesium ppm	Sodium ppm	Nitrogen ppm	Phosphorus ppm	Zinc ppm	TBN (mgKOH/g)	Sulphated Ash %Wt
Euro Trans 75W/80	0.855	63.0	10.6	159	623	3297		1428		1512	1673		1.81
Gear 50-S RoadRanger	0.860	132.0	17.5	146									
SYN EP 75W90	0.864	108.9	16.5	164	520		950		610	1,630			
SYN LS 80W140	0.884	214.8	27.7	166	168				1,530	1,880			0.18
TRANS 90 GL1 (RM300/50)	0.894	215.0	19.8	105		2,330			686	915	1,019	7.36	0.95
TRANS EP 90	0.898	225.6	19.7	100	168				630	980			0.18
TRANS EP 140	0.910	413.6	36.1	130	168				630	980			0.18
TRANS EP 75W90	0.881	88.6	16.7	204	442		808		519	1386			
TRANS EP 80W90	0.898	180.4	17.0	100	168				630	980			0.18
TRANS EP 85W140	0.901	352.5	26.5	100	168				630	980			0.18
TRANS LS 90	0.901	195.0	18.0	101	168				1380	1730			0.18
TRANS LS 140	0.900	422.0	30.0	100	168				2130	2480			0.18
TRANSAXLE 80W90	0.896	103.8	14.3	142	130				790	1700			