

# Boom Grease NLGI 2

## Product Description

**Anglomoil Boom Grease** is an aluminium complex based grease with synthetic base oil and enhanced with PTFE and specially selected additives for use in applications requiring extreme water resistance, high temperatures, presence of dust and other contaminants. Used extensively for sliding surfaces and other high load applications throughout crane and marine industries.

## Product Features

- Non conductive
- PTFE additive added to reduce friction encountered on sliding surfaces
- Provides long term lubrication at high and low temperatures
- Excellent degree of water resistance protecting against corrosion
- Heavy metal free

## Technical Data

Appearance	Off-white Tacky Grease
Solid lubricant	PTFE
NLGI Classification	2
Thickener	Aluminium Complex
Base Oil	PAO Synthetic Oil
Base Oil Viscosity @ 40 °C (IP71) cSt	400
Worked Penetration (IP50)	265 to 295
Dropping Point (IP32) °C	230 min
Oil Separation (IP112)	5 Max.
Resistance to corrosion Emscor (IP 220)	Pass
Water Washout (ASTM D1264) @ 39 °C %	0:0
Operating Temperature Range	-40 °C to + 175 °C

**Master Item# 2402**

**Pack Size Availability: 300g, 400g, 450g, 20kg, 180kg**

**Last Updated: 4<sup>th</sup> March 2021**