

# GardenMaster Bar & Chain Oil

## Product Description

**Anglomoil Chain Oil** is a premium chain oil made with mineral oils, friction modifiers, anti-wear additives and tackifier. It is a high performance product suitable for chains and bars of power chain saws.

## Recommended Applications

- All chains, including oil baths, hand and automatic lubricated
- Bars and chains of high performance professional power chain saws
- Conveyor systems

## Advantages

- Additive system protects the chain, bar and sprockets from wear
- Tacky nature reduces fling-off from the chain
- Green colour helps distinguish this chain oil from engine oils
- Rust Inhibited

## Application of Oil to Industrial Applications

It is essential that lubricant reaches the bearing area of the chain by directing it into the clearances between the inner and outer link plates.

Application method	Power & Speed
Manual	Low
Drip Feed	To 37 kW @ 6 m/s
Oil Bath	To 37 kW @ 10 m/s
Pump & Sump	Drives over 37 kW

## Ambient Temperature

°C	SAE Grade
-5 to + 25	30
25 – 45	40
45 - 65	50

## Typical Characteristics

Properties	
Viscosity @ 40 °C	126
Viscosity @ 100°C	14
Viscosity Index	107
Density @ 2 °C	0.884
SAE Viscosity	30

Master Item# 1601

Pack Size Availability: 1L, 5L, 20L, 200L, IBC=1000L

Last Updated: 28<sup>th</sup> September 2021