



FM WO Hook Oil

ISO 15

Description

FoodMaster (FM) White Oil (WO) Hook Oil is made exclusively from Paraffinic White Oils and special additive packages. These oils are NFS H-1 listed for use where incidental food contact can occur. FM WO Hook Oils are recommended for Hook applications in food processing machinery.

Applications

FM WO Hook Oils are recommended for meat hook in abattoirs.

Certifications

Kosher

- K-ID: RBQ-PTXH

SCHIMA Halal

- Certificate Number: 00562305ASL1-1K

NSF H-1

- 145951

Features & Benefits

- FoodMaster WO Hook Oil is formulated from Paraffinic White Oils with excellent thermal stability and lubricity. Anglomoil's unique additive system further enhances this high performance to offer the best protection for hook applications in the food industry.
- The outstanding corrosion protection properties of FoodMaster WO Hook Oil provide longer service life to hooks in the food industry.
- The thermally and chemically stable formulation offers exceptional service life and superb performance in both high and low-temperature conditions.

Specifications

Properties	Method	Results
Specific Gravity @ 20°C		0.853
Kinematic Viscosity @ 40 °C (cSt)	ASTM D445	13.8 – 16.5
Viscosity @ 100 °C (cSt)	ASTM D445	
Flash Point (°C)	ASTM D92	185
Pour Point (°C)	ASTM D97	-9.4
Polycyclic Aromatic Hydrocarbons	TM 1606	Conform BP
Readily Carbonisable Substances	BP 2002	Conform BP
Solid Paraffin's	BP 2002	Conform BP

Master Item# 2483

Pack Size Availability: 20L, 200L

Last Updated: 18th July 2023

Sydney | Melbourne | Newcastle | New Zealand | Vietnam

Anglomoil Lubricants Group Pty. Ltd. | ABN 83 622 865 091

Int HQ: 2 Beaumont Rd, Mt Kuring-gai NSW 2080 Australia | Australia: P 1300 264 566

Int: P +61 9457 8566 | F +61 2 9457 8057 | E info@anglomoil.com | www.anglomoil.com