

Roadmaster 200

SAE 30 & 50

Product Description

Roadmaster 200 which is available in SAE30 and SAE 50 viscosity grades (see Typical Characteristics table below) meet API SL/CF and ACEA performance specifications.

Product Features & Benefits

Roadmaster 200 is ideal for a 4 stroke lawnmower engines, pumps, generators and older vehicles calling for mono grade oils of SAE 30 or 50 viscosity grades. It is mainly used in garden machinery with petrol engines where manufacturers recommend API SH/SJ or earlier specifications. It is also suitable for diesel units requiring API CD or CF lubricants.

Additional Information

Roadmaster 200 is blended from high quality base oils fortified with a balanced additive package to provide:

- High level of engine protection against engine sludge, varnish deposits and wear
- Reduction in wear in the valve train mechanism
- Increased resistance to oil oxidation
- Excellent carbon deposit control for performance retention over time
- Low temperature fluidity for easy start in cold conditions
- Reduced volatility for low oil consumption

Typical Characteristics

	SAE 30	SAE 50
SG @ 20°C	0.871	0.883
Viscosity @ 40°C	826	176
Viscosity @ 100°C	10.8	17.4
Viscosity Index	117.3	106.9
Phosphorus %Wt	0.11	0.11

Performance Levels

API SL / SJ	API CF
JASO T903: 2011	

Master Item# 1109 & 1111

Pack Size Availability: SAE 30; 1L, 5L, 20L, 200L, IBC=1000L
 SAE 50; 20L, 200L, IBC=1000L

Last Updated: 28th September 2021