

Product Description

Roadmaster RASYN GT 30 is an Ultra High performance synthetic passenger car engine oil formulated to meet the Ford M2C-913D specification as well as meeting the demands of today's most advanced light diesel and petrol engine lubricant specifications. It is a SAE 5W/30 viscosity grade providing excellent fuel efficiency, easier starting due to its low viscosity and improved frictional characteristics.

Product Features & Benefits

Roadmaster RASYN GT 30 was formulated to meet the stringent requirements of the Ford M2C-913D specification and provides:

- Excellent fuel efficiency and easier starting due to its low viscosity and improved frictional characteristics
- Excellent shear stability so that it will stay in grade throughout the recommended oil drain period
- Uses synthetic base stocks for better oxidation stability and providing lower oil volatility minimising oil usage

Roadmaster RasyN GT 30 is intended for use at extended drain intervals in high performance gasoline engines and car & light van diesel engines designed to be capable of using low friction low viscosity oils with a High temperature/ High shear rate (HTHS) viscosity of 2.9 to 3.5cP.

Additional Information

Roadmaster RASYN GT 30 is recommended for:

- Fuel-injected petrol engines fitted with emissions control technology and catalytic converters
- Turbo-charged and intercooled direct injection high performance diesel engines fitted with blow-by recirculation and exhaust

Oils meeting **WSS-M2C913-D**:

- Are recommended for all Ford diesel engines except Ford Ka TDCi models manufactured before 2009 and Ford Galaxy 1.9 TDi models manufactured between 2000 and 2006
- Is especially recommended for diesel engines where M2C913-B or M2C913-C oils were initially required
- Must be used in Ford Transit vehicles manufactured from 2012 onward with Duratorq 2.2 engine
- Can be used with extended oil change intervals and are also suitable to be used in engines running on biodiesel or high sulphur diesel

Typical Characteristics

S.G @ 20°C	0.851	Sulphated Ash %Wt	1.26
KV @ 40°C	63.7	Base No. mg KOH/gm	11.4
KV @ 100°C	11.3	Phosphorus %Wt	0.088
Viscosity Index (Vie)	172.2	Sulphur %Wt	0.233

Performance Levels

API SN / CF	Ford M2C-913-D	MB-Approval 226.5
ACEA A5/B5 – 16 (2016)	Ford M2C-913-C	MB-Approval 229.1
ACEA A3/B4 – 16 (2016)	Ford M2C-913-B	MB-Approval 229.3
BMW Longlife-01	Renault RN0700	MB-Approval 229.5
PSA Peugeot Citroen B712296	Renault RN0710	Volkswagen VW50200 (2005)
Jaguar Land Rover ST JLR.03.5003		Volkswagen VW50500 (2005)

Technical Data Sheet

Master Item# 1134
Pack Size Availability: 20L, 200L

Last Updated: 23rd February 2021