



RM Silver

SAE 15W40

Description

RoadMaster Silver SAE 15W40 is formulated with high performance mineral oils and the latest additive technology to meet API SP/CF Petrol Engine Lubricant specifications which provide excellent engine protection for the modern car requiring an API SP/CF oil.

Applications

RoadMaster Silver SAE 15W40 is suitable for most passenger cars that require API SP/CF specification and is backward compatible with API SM/SL and lower where these oils are called for by OEM. It is also suitable for LPG fuelled engines.

Features & Benefits

API SP gives improved performance in the areas of:

- High temperature deposits protection for pistons
- Better sludge control
- Better seal compatibility
- Aftertreatment compatibility
- Suited for engines that require LSPI protection

RoadMaster Silver 15W40 is blended from high quality base oils fortified with a balance additive package to provide a high level of engine protection against engine sludge, varnish deposits and wear. A particular feature of the RoadMaster Silver specification is the special attention given to the reduction in wear in the valve train mechanism – and increased resistance to oil oxidation.

Specifications

Properties	Method	Result
Specific Gravity @ 20°C	ASTM D1298	0.863
Kinematic Viscosity @ 40°C	ASTM D445	100.7
Kinematic Viscosity @ 100°C	ASTM D445	14.3
Viscosity Index	ASTM D2270	146.5
Sulphated Ash %Wt	ASTM D874	0.87
Total Base No. mg KOH/gm	ASTM D2896-11	7.5
Phosphorus, %Wt	ASTM D3231	0.076
Sulphur, %Wt	ASTM D2622	0.216

Performance Levels

API SP/CF

Master Item# 1003

Pack Size Availability: 20L & 200L

Last Updated: 29th November 2023
Previously Updated: 29th June 2021