

RM Titanium FEO

SAE 5W30

Previously known as RM Platinum FEO SAE 5W30

Description

RoadMaster Titanium FEO SAE 5W30 is an API SP, ILSAC GF-6A, Dexos 1 performance, full synthetic engine oil. It is recommended for vehicles requiring that performance level in order to maximise performance and engine life.

Applications

RM Titanium FEO assists in preventing deposits in the engine and turbocharger to ensure full boost pressure, whilst maintaining engine power and fuel economy. Suitable for most high-performance petrol engines in passenger cars where a low viscosity oil is required, especially when equipped with exhaust catalyst systems

Features & Benefits

The **RM Titanium FEO** formulation was especially developed as a full synthetic to take advantage of the extra oxidative stability and low temperature properties that they provide. This specific formulation provides:

- Superb oil performance and protection to help improve engine durability
- Improved oxidation and wear performance over conventional motor oils, which provides improved fuel economy
- Piston cleanliness delivers maximum engine performance
- Low volatility delivers reduced oil consumption
- Great viscosity control helps to deliver improved fuel efficiency
- GM-specified oil for 2011 vehicles with gasoline engines
- Suitable for engines that require LSPI (Low-Speed Pre-Ignition) protection

Specifications

Properties	Method	Result
Specific Gravity @ 20°C	ASTM D1298	0.848
Kinematic Viscosity @ 40°C	ASTM D445	61.7
Kinematic Viscosity @ 100°C	ASTM D445	10.7
Viscosity Index	ASTM D2270	165.8
Sulphated Ash %Wt	ASTM D874	0.84
Total Base No. mg KOH/gm	ASTM D2896-11	8.7
Phosphorus (ppm)	ASTM D3231	763
Sulphur (ppm)	ASTM D2622	2141

Performance Levels

GM Dexos 1 (SFU)	Ford M2C-961-A	ILSAC GF-6A
API SP/CF	Chrysler MS-6395	Energy Resource Conserving
ACEA A3/B4 – 21 (2021)	GM 6094M	Ford M2C-946-B1



RM Titanium FEO

SAE 5W30

Previously known as RM Platinum FEO SAE 5W30

Additional Information

RM Titanium FEO 5W30 also:

- Provides outstanding high-temperature protection
- Resists degradation even at high RPMs
- Advanced synthetic formulation helps to extend engine life and keep your engine running in optimum condition
- Flows freely in extremely cold weather, reducing engine wear during winter start-ups
- Meets and exceeds industry standards
- 5W30 meets and exceeds Dexos 1 specifications



Master Item# 1181

Pack Size Availability: 20L, 200L & IBC = 1000L

Last Updated: 30th November 2023

Previously Updated: 9th May 2023

Sydney | Melbourne | Newcastle | New Zealand | Vietnam
AnglomOil Lubricants Group Pty. Ltd. | ABN 83 622 865 091

Int HQ: 2 Beaumont Road, Mt. Kuring-gai NSW 2080 Australia | Australia: P 1300 264 566
Int: P +61 2 9457 8566 | F +61 2 9457 8057 | E info@anglomoil.com | W www.anglomoil.com