

Product Description

Vac 10 is a Semi-Synthetic Hydraulic and Vacuum oil with boosted corrosion inhibition and moisture repellent properties for application in a range of forklift trucks.

Product Features & Benefits

Vac 10 gives:

- **Durability** retains performance after extended use which helps to extend both oil and equipment life.
- **Hydrolytic Stability** protects equipment from corrosion when water is present.
- **Wet and Dry Filterability**, reduces filter changes and sluggish system performance
- **Thermal and Oxidative Stability** reduces formation of sludge and varnish thereby reducing potential downtime.
- **Demulsibility**, improved water shedding properties helping to prevent rust.
- **Rust Protection** inhibits rust formation leading to extended equipment life and lower overall costs.
- **Low Foam**, reduced foaming tendencies reduce inadequate lubrication and potential pump damage

Additional Information

Vac 10 meets the needs of hydraulic equipment operating under medium to severe service conditions.

Typical Characteristics

Test	Test Method	Result
Density @ 20 °C	IP 160	0.839
Viscosity @ 40°C	IP 71	10.0 cSt
Viscosity @ 100°C		2.7 cSt
Viscosity Index	IP 226	110

Performance Levels

Denison HF-0, HF-1, HF-2	DIN 51542 Part2	AFNR NFE 48-690 (dry)
Eaton Vickers I-286-S and M-2950-S	Sauer Danfoss	AFNOR NFE 48-691 (wet)
Cincinnati Machine P-68, P-69, P-70	Bosch Rexroth	JCMAS HK
US Steel 127 and 136	Commercial Hydraulics	
General Motors LH-03-1, LH-04-1, LH-06-1	<i>(Except for PM-500 series silver containing pumps)</i>	

Master Item# 1761

Pack Size Availability: 20L, 200L, IBC=1000L

Last Updated: 9th March 2021