

## Product Description

Vac 30 is zinc-based premium antiwear hydraulic and vacuum oil developed for both high and low pressure hydraulic systems for industrial and mobile applications. Anglomoil's Vac 30 exhibits excellent durability and proven retention of performance that extends fluid and equipment life.

## Product Features & Benefits

- Exceptional wear and protection exceeds standard industry limits and extends the useful life of the system components.
- Maximum seal protection saves money and simplifies maintenance by preventing loss of fluid through leaks.
- Outstanding oxidative and thermal stability allows use in the harshest operation conditions.
- Proven performance in the field ensures confidence and peace of mind.
- Suitability with a range of global Group I, II and III base oils offer formulating flexibility.

## Typical Characteristics

Characteristics	Typical Value	Unit	Method
Colour/Appearance	Dark Amber	-	-
Specific Gravity @ 15.6°C	1.023	SPGRAV	ASTM D 1298
Viscosity @ 40°C	65	CST	ASTM D 445
Viscosity @ 100°C	8	CST	ASTM D 445
Flash Point, °C, PMCC	110	°C	ASTM D 93
Pour Point, °C	-24	°C	ASTM D 97
Calcium	0.48	%	LZ Test Method
Nitrogen	0.14	%	LZ Test Method
Phosphorus	3.9	%	LZ Test Method
Sulphated Ash	13.5	%	ASTM D 874
Sulphur	7.7	%	LZ Test Method
Zinc	4.87	%	LZ Test Method

## Performance Levels

Bosch Rexroth RDE-90235	Eaton Brochure 03-401-2010
Eaton Lubricant Specification E-FDGN-TB002-E	JCMAS HK P041
Parker Denison HF-1, HF-2, HF-0	Eaton Vickers I-286-S, M-2950-S

Master Item# 1763  
 Pack Size Availability: 20L

Last Updated: 19<sup>th</sup> August 2022