

WO Chain Oil

ISO 220

Product Description

Anglomoil WO Chain Oil 220 is made from Paraffinic white Oils and special additive packages and are NFS H-1 listed for use where incidental food contact can occur. WO Chain Oil is a non-toxic, water resistant lubricant recommended for all types of chain and conveyor applications in food processing machinery, pharmaceutical and other clean environments.

Product Features & Benefits

Anglomoil WO Chain Oil is formulated from Paraffinic white Oils and have good thermal stability and lubricity. This high performance is further enhanced by Anglomoil's unique additive system.

Anglomoil WO Chain oil provides

- Good service life.
- Excellent corrosion and wear protection to the chain which minimizes down time and provides longer chain service life.
- Excellent adhesive properties which allow the lubricant to cling to the chain in use and resist water wash off in both cold and hot water.
- Good high and low temperature operations.
- Good oxidative stability.
- Easy application by brush, bath or automatic lubrication system.
- Solvent free formulation for greater safety in storage and use

Approvals

- NSF H1 Listing # 145946
- HALAL Approved

Compatibility

Anglomoil white oil based lubricants are similar to mineral oils in their compatibility with paints, seals, gaskets and hoses. No special precautions related to compatibility are required when changing over from a mineral oil lubricant to an Anglomoil white oil hydrocarbon-based lubricant.

Typical Characteristics

ISO Grade	220
NSF H1 Listing #	145946
Base Fluid	White Oil
Flash Point °C	>180 °C
S.G. @ 15.6 °C	0.86
Viscosity @ 40°C	220
Viscosity @ 100°C	20.5
Viscosity Index	109

Master Item# 2477

Pack Size Availability: 20L, 200L

Last Updated: 26th July 2021