

## Product Description

Anglomoil WO Hook Oil is made from Paraffinic white Oils and special additive packages and are NFS H-1 listed for use where incidental food contact can occur. WO Hook Oils are recommended for Hook applications in food processing machinery.

## Product Features & Benefits

Anglomoil WO Hook Oil is formulated from Paraffinic white Oils and have good thermal stability and lubricity. This high performance is further enhanced by Anglomoil's unique additive system.

Anglomoil WO Hook oils will provide:

- Good service life.
- Excellent corrosion protection to the Hook providing longer service life
- Good high and low temperature operations
- Good oxidative stability

## Compatibility

Anglomoil white oil based lubricants are similar to mineral oils in their compatibility with paints, seals, gaskets and hoses. No special precautions related to compatibility are required when changing over from a mineral oil lubricant to an Anglomoil white oil hydrocarbon-based lubricant.

## Typical Characteristics

	Method	ISO 15
NSF Listed #		145951
Appearance		Water White
Colour	Saybolt	+ 30 min
Brookfield Viscosity 40°C cPs	TM 2201	Report
Kinematic Viscosity at 40°C cSt	ASTM D445	13.8 – 16.5
Pour Point	ASTM D97	-9.4 °C typ
Flash Point	ASTM D92	185 °C typ
Polycyclic Aromatic Hydrocarbons	TM 1606	Conform BP
Readily Carbonisable Substances	BP 2002	Conform BP
Solid Paraffin's	BP 2002	Conform BP
Specific Gravity		0.853 typ

Master Item# 2483

Pack Size Availability: 20L, 200L

Last Updated: 26<sup>th</sup> July 2021