

Nickel Anti-Seize Grease

Product Description

Anglomoil's Nickel Anti-Seize Grease is formulated with mineral oil and organo-clay (bentonite) thickener. it provides maximum protection in highly corrosive environments and assemblies exposed to extreme temperatures (1300 °C).

Product Features & Benefits

- Excellent protection during extreme temperature operation
- Extended service life
- Seizing prevention

Applications

- For use on stainless steel and similar alloys
- Protection for threaded fasteners and fittings
- Spark plug threads
- Can serve as good electrical conductor

Typical Characteristics

	Test Method	Typical Results
Thickener Type	-	Clay - Bentonite
Colour/Appearance	-	Silver/Flecked
Worked Penetration (60 Strokes)	ASTM D217	290 – 320
Dropping Point (°C)	ASTM D2265	Does not melt
Base Oil Viscosity @ 40°C (cSt)	ASTM D445	500
Solid Content (%wt)	-	13

Master Item# 1825 Pack Size Availability: 20kg, 180kg

Last Updated: 15th March 2023

Sydney | Melbourne | Newcastle | New Zealand | Vietnam AnglomOil Lubricants Group Pty. Ltd. | ABN 83 622 865 091 Int HQ: 2 Beaumont Road, Mt. Kuring-gai NSW 2080 Australia | Australia: P 1300 264 566 Int: P +61 2 9457 8566 | F +61 2 9457 8057 | E info@anglomoil.com | W www.anglomoil.com

Technical Data Sheet

l|Page