

# ANGLOMOIL WATER DISPERSANT

## Technical Data Sheet

### Product Description

**Anglomoil Water Dispersant** is a heavy duty water dispersant designed to displace moisture and assist in lubricating, protecting and starting wet motors. The product is suitable to be used on most machinery parts, heavy duty engines and hobby engines. It is fast acting in displacing moisture from engines and motor parts and protects against corrosion. Anglomoil Water Dispersant also stops squeaks and loosens rust parts.

### Directions For Use

To enable Anglomoil Water Dispersant to penetrate engine parts quickly and efficiently remove as much as possible of the trapped dirt, dust and other contaminants from the surface by scraping or wiping with a rag. Repeat if necessary until surface is clean. Shake the can for about 1 minute to ensure uniformity of contents. For lubrication apply liberally onto the affected parts. To effect maximum penetration and corrosion protection, apply additional coats and allow to stand for several minutes. Spray periodically as required.

### Usage

Under normal usage the Anglomoil Water Dispersant will provide up to 350 spray applications per 400 gram can. Usage will also be dependent on the duration of the spray.

### Workability

When used to start up motors the Anglomoil Water Dispersant the actives will immediately displace moisture from the surface. The product also contains special oils that quickly coat the metal surface thus sealing out potential moisture and preventing corrosion. The oils used also have lubricating properties that are very effective at silencing ongoing squeaks. Anglomoil Water Dispersant will displace moisture instantly from the surface and will maintain the surface moisture resistant for at least 10 hours. For very wet conditions and where the vehicle had traveled through puddles of water it may be necessary to saturate the surface with Anglomoil Water Dispersant to displace water.

### Pack Size

400 grams (CTN/12)

PART# 2866400



LAST UPDATED 29 AUG 2019