

Anglomoil Red Engine Coolant is a Long Life Concentrated Anti-Freeze/Anti-Boil Corrosion Inhibitor. It is recommended for the protection of cooling systems of late model petrol and diesel engines operating in all conditions

Anglomoil Red Engine Coolant uses Organic Acid Technology (OAT) carboxylate corrosion inhibitors. Its advantage is that it provides a longer storage life than most other coolants. This allows maximum corrosion and anti-freeze/anti-boil protection for up to 250,000 Km or Five years*.

Anglomoil Red Engine Coolant is silicate free and contains no nitrite, phosphate or amine. Anglomoil Red engine coolant is the preferred coolant for cooling systems fitted with aluminum radiators. It is a 100% OAT based, long life coolant.

Anglomoil Red Engine Coolant is dyed red to distinguish it from traditional green coolants and is recommended for cooling systems that use red coloured coolant. It is designed for use where OAT coolant is required and particularly suited for use where AS/NZ 2108.1:1997 Type A, GM6277M or Toyota TSK2601G Specifications are required.

Anglomoil Red Engine Coolant can be diluted at 33% to 50% with soft or demineralised water, however it is recommended that you should check the engine manufactures recommendation.

Mix Ratio	Makes	Boils at	Freezes at
33.3%	1 Litre makes 3 Litres	127 °C	-18°C
50%	1 Litre makes 2 Litres	130°C	-37°C

Anglomoil Red Engine Coolant should not be mixed with other coolants and you should always thoroughly flush the system before use to avoid contamination that will reduce coolant life..

Anglomoil Red Engine Coolant is available in 20 & 205 Litre Drums.

Recommended Against the Following Standards and Recommendations			
AS/NZS 2108.1: 1997 Type A	SAE J 1034	BS 6580	Volvo UK
ASTM D 5345	General Motors GM 1825M	JIS K 2234	BMW UK
ASTM D 4340	General Motors Holden GM 6277M	Mitsubishi ES-X64217	Saab FSD 8074
ASTM D 3306	General Motors Holden GM 1899M	Nissan NES M 5509	Daimler Chrysler MS-7170
ASTM D 4985	Ford ESE-M97B44-A (Auto)	Ford WSS-M97B44-D	Daimler Chrysler MS-976
ASTM D 4656	Ford ESE-FM97B18-C	Mazda MES MN 121D	Toyota TSK2601G
AS 2108.84	ASTM D 2570	ASTM D 1384	ASTM D 2809

* which ever comes first.

PRODUCT DATA SHEET

Anglomoil Superior Lubricants

Lubricants for Automotive - Industry - Food - Farm Machinery - Marine - Earthmovers - Road Transport

2 Beaumont Rd, Mt Kuringai, NSW, Australia Phone: +61 2 9457 8566, Fax: +61 2 9457 8057 Email: info@anglomoil.com Web: www.anglomoil.com