

Product Description

Anglomoil Slideway Oil series are high performance, ashless slideway lubricants based on solvent refined mineral oils.

Product Features & Benefits

Anglomoil Slideway Oil's utilise the proven technology in lubricity, extreme pressure and demulsibility to provide optimum performance in use. They have:

- Strong demulsibility and water separation performance
- Proven stick slip performance which is required for repeatable machining.
- Exceptional anti-staining and anti-corrosion properties
- Light colour and low odour
- Excellent anti-wear and extreme pressure performance
- Non-corrosive to both ferrous and non-ferrous alloys.
- Excellent filterability
- Compatibility with commonly used cutting fluids

Additional Information

Anglomoil Slideway Oils

- are recommended for both vertical and horizontal slideways where high quality demulsifying slideway lubricants are required.
- Can be used for both metal and plastic slideways.

Typical Characteristics

Test	Test Method	68	220
Physical Properties			
Density @20°C	IP 160	0.878	0.893
KV @ 40°C	ASTM D445	72.5 cSt	214 cSt
KV @100°C	ASTM D445	9.5 cSt	19.2 cSt
VI	IP 226	109	101

Performance Levels :

Anglomoil Slideway Oils meet all the requirements for

Slideway Lubricant	Cincinnati Lamb P-47
Hydraulic and Industrial Gear Oil	DIN 51524-2 HLP DIN 51517-3 CLP
Additional Performance	Bijur Filtration Testing SKC Coolant Separability Darmstadt Test Protocols

Anglomoil Superior Lubricants

Lubricants for Automotive - Industry - Food - Farm Machinery - Marine - Earthmovers - Road Transport
2 Beaumont Rd, M1 Kuringgai, NSW, Australia Phone: +61 2 9457 8566, Fax: +61 2 9457 8057 Email: info@anglomoil.com Web: www.anglomoil.com